

24P 10/100M switch

Model:ATS-2400D

Complies with IEEE 802.3, IEEE 802.3u standards

24 10/100Mbps Auto-Negotiation RJ45 ports supporting Auto-MDI/MDIX

Supports IEEE 802.3x flow control for Full Duplex mode

and backpressure for half-duplex mode

Supports MAC address auto-learning and auto-aging

LED indicators for monitoring power, link, activity,

100Mbps

Standard 14-inch rack-mountable steel case

Universal power supply, External (-48 Volt)



Specification:

Network protocol		IEEE802.3 10Base-T, IEEE802.3u 100Base-TX
Port		24 10/100Mbps Auto-Negotiation RJ45 ports supporting Auto MDI/MDIX
Network Media		10Base-T:UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100Base-Tx:UTPcategory 5 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Filter and transmission rate		10Mbps : 14880pps 100Mbps : 148800pps
LED Indicator	Each port	Link/Act, 10M/100M,
	Others	Power
Dimension(L x W x H)		420 x 168 x 44mm
Environment		Operation Temperature : 0°C-40°C ; Store Temperature : -40°C-70°C Operation Humidity : 10%-90% RH Non-condensing ; Store Humidity : 5%-90% RH Non-condensing
Power		- 48 V DC

ANDA Telecom Pvt. Ltd.

ISO 9001:2000 Certified Company

Registered office : E-36, Amar Colony, Lajpat Nagar-IV, New Delhi - 110024, INDIA

Phone : +91 11 41323629, +91 93 502 57173

E-mail : Info@andatelecomindia.com

URL : www.andatelecomindia.com