







ATS-3000(B) SERIES

Overview

AT ATS3000(B) series is an excellent choice as access layer switch for education, government and large/medium enterprise networks. With different customer requirements, the ATS3000(B) series access switch provides standard, enhance and POE types to meet different requirements. AT ATS3000(B) is composed of ATS3008T(B), ATS3016T(B), ATS3024T(B), ATS3009TS(B), ATS3026TS(B) and ATS3009TS-POE(B).

Specification

Model	ATS3008T(B)	ATS3016T(B)	ATS3024T(B)
Feature			
Hardware Feature			
Product image			
Fixed port	8x10/100Base-TX	16x10/100Base-TX	24x10/100Base-TX
Switching capacity	1.6Gbps	3.2Gbps	4.8Gbps
Forwarding performance	1.2Mpps	2.4Mpps	3.6Mpps
Power	AC : 100~240 V AC, 50/60 Hz		
Maximum power consumption	20W		
Relative Humidity	10 ~ 90%(non-condensing)		
Operating temperature	0 ~ 45° C		
Dimension(W*D*H)	283x178x44(mm)		443x231x44(mm)
Model	ATS3009TS(B)	ATS3026TS(B)	ATS3009TS-POE(B)
Feature			
Hardware Feature			
Product image			
Fixed port	8x10/100Base-TX +	24x10/100Base-TX +	8x10/100Base-TX + 1x

ANDA Telecom Pvt. Ltd.


ISO 9001:2000 Certified Company

Registered office : E-36, Amar Colony, Lajpat Nagar-IV, New Delhi - 110024, INDIA

Phone : +91 11 41323629, +91 93 502 57173

E-mail : Info@andatelecomindia.com

URL : www.andatelecomindia.com



ISO 9001:2000 Certified Company

	1xGigabits Combo(SFP/GT)	2xGigabits Combo(SFP/GT)	Gigabits Combo(SFP/GT)
Switching capacity	3.6Gbps	8.8Gbps	3.6Gbps
Forwarding performance	2.7 Mpps	6.6Mpps	2.7 Mpps
Power	AC : 100~240 V AC, 50/60 Hz		
Maximum power consumption	20W		160W
Relative Humidity	10 ~ 90%(non-condensing)		
Operating temperature	0 ~ 45° C		
Dimension(W*D*H)	283×178×44(mm)	443×231×44(mm)	283×178×44(mm)
Service Feature			
Bandwidth Management	64Kbps step		
Switching mode	Store and Forward		
Port feature	Supports IEEE802.3x flow control(full duplex) Support HOL preventing first packet congestion, backpressure Support broadcast pass permission rate can be set Support Jumbo frame		
MAC	Supports 8K MAC addresses		
Port aggregation	Supports Support 802.3ad Supports 14 aggregation groups Up to 8 ports in each aggregation per group		
VLAN feature	Supports VLAN based on port(4000) Supports VLAN based on 802.1Q Supports PVLAN Supports Multicast Vlan		
L2 ring network feature	Supports STP, RSTP, MSTP Support Root guard and BPDU gurad		
Multicast	IGMP v1/v2/v3 snooping, Multicast Vlan Register		
DHCP	Support DHCP server/Client Support DHCP option 82 Support DHCP snooping		
Mirroring	Supports N: 1 port mirroring		
QoS	4 queues per port support WRR/SP support 802.1p, ToS, IPv4/IPv6 DifferServ		

ANDA Telecom Pvt. Ltd.

ISO 9001:2000 Certified Company

Registered office : E-36, Amar Colony, Lajpat Nagar-IV, New Delhi - 110024, INDIA

Phone : +91 11 41323629, +91 93 502 57173

E-mail : Info@andatelecomindia.com

URL : www.andatelecomindia.com



ISO 9001:2000 Certified Company

Security	ARP rate limit ARP bind L2 ports ARP re-authentication Static ARP Support 802.1x Support RADIUS and TACACS+ Support standard ACL&extended ACL, support IP ACL、 MAC ACL、 IP-MAC ACL, support data packet filtering on the basis of source/destination IP address, source/destination MAC address, IP type, TCP/UDP port number, IP precedence, time range, ToS. Support sFlow
Management and maintenance	Supports FTP/ TFTP load update, Supports configuration through command line interface(CLI), telnet, console,WEB, HTTPS and SSL Supports SNMP v1/v2/ v3 Supports RMON I (Remote Monitoring)1/2/3/9 groups of MIBs Supports RMON II

Order Information

Model	Description
Chassis	
ATS3008T(B)	ATS3008T(B)Ethernet Switch Chassis(8x10/100Base-T,AC power supply)
ATS3016T(B)	ATS3016T(B) Ethernet Switch Chassis(16x10/100Base-T,AC power supply)
ATS3024T(B)	ATS3024T(B)Ethernet Switch Chassis(24x10/100Base-T,AC power supply)
ATS3009TS(B)	ATS3009TS(B)Ethernet Switch Chassis(8x10/100Base-T+1xGigabit Combo (SFP/GT) ports AC power supply)
ATS3026TS(B)	ATS3026TS(B)Ethernet Switch Chassis(24x10/100Base-T+2xGigabit Combo (SFP/GT) ports, AC power supply)
ATS3009TS-POE(B)	ATS3009TS-POE(B)Ethernet Switch Chassis(8x10/100Base-T[supports 802.3AF+1xGigabit Combo (SFP/GT) ports, AC power supply)

ANDA Telecom Pvt. Ltd.

ISO 9001:2000 Certified Company

Registered office : E-36, Amar Colony, Lajpat Nagar-IV, New Delhi - 110024, INDIA

Phone : +91 11 41323629, +91 93 502 57173

E-mail : Info@andatelecomindia.com

URL : www.andatelecomindia.com